



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-8501AU2200

Registration Number
Registriernummer

| | |
|---|--|
| Field of Application <i>Anwendungsbereich</i> | products of water supply <i>Produkte der Wasserversorgung</i> |
| Owner of Certificate <i>Zertifikatinhaber</i> | REHAU AG + Co Ytterbium 4, D-91058 Erlangen |
| Distributor <i>Vertreiber</i> | REHAU AG + Co Ytterbium 4, D-91058 Erlangen |
| Product Category <i>Produktart</i> | installation systems with special pipes: drinking water installation systems (8801) |
| Product Description <i>Produktbezeichnung</i> | drinking water installation system consisting of pushing sleeve connectors made of metal (brass, red brass, stainless steel) respectively made of plastic (PPSU) and pipes made of plastic (PE-Xa) |
| Model <i>Modell</i> | RAUTITAN flex |
| Test Reports <i>Prüfberichte</i> | supplement test: 129715/18-I from 30.01.2019 (SKZ) supplement test: 116335/15 from 28.11.2017 (SKZ) supplement test: 116705/15 from 09.03.2017 (SKZ) supplement test: 108990/13-I from 26.06.2014 (SKZ) laboratory control test: 370314/1.1/110900 from 25.06.2014 (SKZ) laboratory control test: 269714/1.1/110901 from 25.06.2014 (SKZ) |
| Test Basis <i>Prüfgrundlagen</i> | DVGW W 534 (01.05.2004) DVGW CERT ZP 8500 (09.03.2017) UBA METALLE (21.11.2018) UBA KTW (07.03.2016) DVGW W 270 (01.11.2007) |
| Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i> | 20.09.2024 / 19-0298-WNR |

70028-04-A-DE

22.04.2020 GI A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

| Type Typ | Technical Data Technische Daten | Remarks Bemerkungen |
|-----------------------------------|------------------------------------|------------------------|
| RAUTITAN flex | diameter: 12 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 16 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 20 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 25 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 32 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 40 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 50 mm | |
| RAUTITAN flex / RAUTITAN pink+ | diameter: 63 mm | |

| Type Variation Ausführungsvariante | Explanations Erläuterungen |
|---------------------------------------|-------------------------------|
| RAUTITAN flex RAUTITAN pink+ | |

certified Components

zertifizierte Bauteile / Werkstoffe

| Registr. No. Registr.-Nr. | Component Bauteil (Produktart) | Model/Type Modell/Typ | Manufacturer Hersteller |
|------------------------------|-----------------------------------|---|----------------------------|
| DW-8301AG2102 | PE-Xa pipe, manufacturing group 1 | PE-Xa-Rohr "REHAU"/PE-Xa-Rohr "REHAU" | REHAU AG + Co |

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

pipe to use: PE-Xa with oxygen impermeable layer, REHAU AG + Co, D - 94234 Viechtach
 pipe to use: PE-Xa with oxygen impermeable layer, REHAU AG + Co, D - 07819 Triptis
 pushing sleeve connector to use (12, 16, 20, 25, 32, 40, 50 and 63 mm): brass,
 type M-MK, D - REHAU AG + Co, D - 07819 Triptis
 pushing sleeve connector to use (16, 20, 25, 32 and 40 mm): stainless steel,
 type M-MK, REHAU AG + Co, D-07819 Triptis
 pushing sleeve connector to use (16, 20, 25, 32 and 40 mm): plastic (PPSU),
 type M-KK, REHAU AG + Co, D-07819 Triptis
 pushing sleeve connector to use (16, 20, 25, 32, 40, 50 and 63 mm): red brass,
 type M-MK, D - REHAU AG + Co, D - 07819 Triptis