



Kolena RAUTITAN, Cevne vodice za sanitarne instalacije

Koleno RAUTITAN PX, 90°

Sa ispuštima za centriranje, univerzalno primenljivo za instalacije pitke vode i grejanja sa univerzalnim cevima RAUTITAN stabil i RAUTITAN flex.

Materijal: PPSU

Boja: crna





Koleno RAUTITAN RX+, 90°

Univerzalno primenljivo za instalacije pitke vode i grejanja sa univerzalnim cevima RAUTITAN stabil i RAUTITAN flex.

Materijal: crveni liv bez olova prema DIN SPEC 2701

Boja: crveni liv blank





Mat.-Nr.	Dimenzija	Tip	Mere mm		Masa kg/kom.	Jedinica isporuke
			a	z		
1160021001	16 - 16	PX	38	24	0,012	10 kom.
11600221001	20 - 20	PX	43	26	0,019	10 kom.
11600231001	25 - 25	PX	53	30	0,031	10 kom.
11600241001	32 - 32	PX	65	34	0,056	3 kom.
11600251001	40 - 40	PX	75	43	0,105	3 kom.
14563071001	50 - 50	RX+	87	48	0,854	1 kom.
14563081001	63 - 63	RX+	106	60	1,365	1 kom.

Koleno RAUTITAN PX, 45°

Sa ispuštima za centriranje, univerzalno primenljivo za instalacije pitke vode i grejanja sa univerzalnim cevima RAUTITAN stabil i RAUTITAN flex.

Materijal: PPSU

Boja: crna





Koleno RAUTITAN RX+, 45°

Univerzalno primenljivo za instalacije pitke vode i grejanja sa univerzalnim cevima RAUTITAN stabil i RAUTITAN flex.

Materijal: crveni liv bez olova prema DIN SPEC 2701

Boja: crveni liv blank



Mat.-Nr.	Dimenzija	Tip	Mere mm		Masa kg/kom.	Jedinica isporuke
			a	z		
11600521001	20 - 20	PX	38	21	0,017	10 kom.
11600531001	25 - 25	PX	46	23	0,028	10 kom.
11600541001	32 - 32	PX	60	28	0,052	3 kom.
11600551001	40 - 40	PX	66	34	0,095	2 kom.
14563091001	50 - 50	RX+	67	28	0,725	1 kom.
14563101001	63 - 63	RX+	80	34	1,185	1 kom.