

## **DECLARATION OF PERFORMANCE**

DoP No.: **W4-FEF-600** 

Unique identification code of the product-type:

W4-FFF-006

Type or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**INSUL-TUBE® HiTemp** Pipe:

For batch or serial N° see label.

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal insulation products for building equipment and industrial installations

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): nmc Polska Sp. z o.o. ul. Pyskowicka 15, 41-807

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Non applicable** 

6.

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

3

In case of the declaration of performance concerning a construction product covered by a harmonised standard (Notified institute, Task, Certificate): IMBIGS-NB 1454- 82/13; 117/13/M-3/O/GII; 73/13/M-3/Aot

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Non applicable

9. Declared performances according to PN-EN 14304+A1:2013-07

Characteristics Performances

4.2.1 Thermal conductivity (W/m\*K) 0 15 °C 40 °C 75 °C 0,041 0,043 0,045

4.2.2 Dimensions and tolerances

see label for nominal values of dimensions see standard for tolerances

4.2.3 Dimensional stability

4.2.4 Reaction to fire:

Thickness

13-19mm

Euroclass

Е

4.2.5 Durability characteristics

4.3.2 Maximum service temperature 4.3.3 Minimum service temperature 4.3.4 Water absorption

4.3.5 Water vapour diffusion resistance
4.3.6 Trace quantities of water soluble ions and the pH-value

4.3.7 Structure-borne sound transmission

4.3.8 Sound absorption

4.3.9 Release of dangerous substances

4.3.10 Continous glowing combustion

NPD

NPD ST(+) +150°C ST(-) 0°C WS01

MU 4500 NPD

NPD NPD NPD

10.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsability of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Name and function :

Zabrze, the. 08-07-2014



Inside Sales Coordinato



