

## Odlične performanse i jedinstveni dizajn sada i u vašem domu

Izuzetan dizajn zajedno sa odličnim performansama izdvajaju ovaj uređaj i čine ga jedinstvenim među mnoštvom drugih klima uređaja



### Ukratko

- ▶ Odlična inverter klima po super ceni
- ▶ Wi-Fi upravljanje preko Bosch HomeCome Easy aplikacije (uz gateway kao dodatni pribor)
- ▶ Mnoštvo funkcija u skladu sa vašim potrebama (defrost, zaštita od korozije, Eco Mode, stand-by 1W)
- ▶ Povećana higijena prostora (HD filter, i-clean tehnologija)



#### Auto Restart

Vaš klima uređaj neće zaboraviti podešavanja koja ste mu zadali pre nestanka struje



#### i-clean

Ubija i do 99% bakterija zagrevanjem isparivača na temperaturu od 56°C



# Climate 3000i

## Hlađenje



A+++ → D

## Grejanje



A+++ → D



## Funkcije:



Wi-Fi



Follow me funkcija



Izbegavanje direktnog strujanja



Antikorozijska



Nisko ambijentalno hlađenje



8° grejanje



Dry mode



Promena brzine ventilatora



Eco mode



Jedinstveni Bosch dizajn, estetski prijatan: spoljna jedinica neće remetiti izgled vaše zgrade.

Tehničke karakteristike			Climate 3000i			
			CL3000i-Set 26 E	CL3000i-Set 35 E	CL3000i-Set 53 E	CL3000i-Set 70 E
Hlađenje	Nominalna snaga	kW	2,8	3,6	5,3	7,0
	SEER	W/W	7,4	7,0	7,0	6,4
	Klasa energetske efikasnosti		A++	A++	A++	A++
Grejanje (prosečna sezona)	Nominalna snaga	kW	2,5	2,5	4,2	4,9
	SCOP	W/W	4,1	4,2	4,0	4,0
	Klasa energetske efikasnosti		A+	A+	A+	A+
Grejanje (toplija sezona)	Nominalna snaga	kW	2,5	2,5	4,5	5,3
	SCOP	W/W	5,2	5,5	5,1	5,1
	Klasa energetske efikasnosti		A+++	A+++	A+++	A+++
<b>Unutrašnja jedinica</b>						
Unutrašnja jedinica	Dimenzije (Š*D*V)	mm	729x200x292	802x200x295	971x228x321	1082x234x337
Visina zvučnog pritiska/nivo buke (viši/srednji/niži/noću)		dB(A)	37/32/22/20	37/32/22/21	41/37/31/20	46/37/34.5/21
Nivo zvučne snage		dB(A)	54,0	56,0	56	62
Protok vazduha (veliki/srednji/mali)		m3/h	520/460/330	530/400/350	800/600/500	1090/770/610
<b>Spoljašnja jedinica</b>						
Spoljašnja jedinica	Dimenzije (Š*D*V)	mm	720x270x495	720x270x495	805x330x554	890x342x673
Visina zvučnog pritiska/nivo buke		dB(A)	55,5	55,0	57	60
Nivo zvučne snage		dB(A)	62	63	65	67
Optimalni radni opseg temperature spolj. jedinice (hlađenje/grejanje)		°C	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24
Hlađenje	Nominalna snaga (min-max)	Btu/h	9000 (3500-11000)	12000 (4700-14700)	18000 (7200-20130)	24000 (11570-28000)
Grejanje	Nominalna snaga (min-max)	Btu/h	10000 (2800-11500)	13000 (3650-14950)	19000 (5300-19960)	25000 (10580-28000)
Rashladno sredstvo	Tip		R32	R32	R32	R32
	Potencijal glob. zagrevanja GWP	kgCO <sub>2</sub> eq	675	675	675	675
	Fabričko punjenje	Kg	0,6	0,65	1,1	1,45
Crevo rashladnog fluida	Max dužina creva između ODU i IDU	m	25	25	30	50
	Max. visinska razlika	m	10	10	20	25
Napajanje	Ph-V-Hz		220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz